PIG® Heavy-Duty Poly Spill Containment Pallet

#PAK987 - 61-gal. capacity, choose w/ or w/out drain





Your heaviest drums are safe and sound on our heavy-duty pallets. They're the strongest and lowest-profile on the market!

- Strong enough for long-term storage of liquids with high specific gravities
- Innovative design transfers weight to load-bearing channels to maximize capacity
- Molded-in sump catches leaks, drips and spills to help you comply with regulations and keep your storage areas clean and safe
- Low height means loading and unloading require less effort and drum tops are within easier reach
- Low-density polyethylene (LDPE) construction resists UV rays, rust, corrosion and most chemicals
- Textured grating adds traction and lifts out for easy sump access
- Optional drain plug lets you empty sump without removing drums or grating
- 2-way forklift entry allows easy movement from either direction (loaded or unloaded)
- We test all of our PIG Containment Pallet designs at max load for months to ensure they can handle full capacity at your facility

PAK987 Product Option Information

Item #	Description	Dimensions	Weight
PAK987-BK-WD	Black, With Drain	40" W x 40" L x 12.5" H	53 lbs.
PAK987-BK-WOD	Black, Without Drain	40" W x 40" L x 12.5" H	53 lbs.

Metric Equivalentem #	ent Description	Dimensions	Weight
PAK987-BK-WD	Black, With Drain	101.6cm W x 101.6cm L x 31.8cm H	24 kg
PAK987-BK-WOD	Black, Without Drain	101.6cm W x 101.6cm L x 31.8cm H	24 kg

PAK987 Specifications

Recycled Content: 30% Post-Industrial Recycled Polyethylene

Load Capacity UDL: 800 lbs. Sump Capacity: 61 gal.

Capacity: One 55-gal. Steel or Poly Drum

Drain: Optional

Fork Truck Access: Two-way, Can Move Loaded

Grates: One 26" L x 26" W

Sold as: 1 each # per Pallet: 10

Composition: Sump - Linear

Low-Density Polyethylene with UV Inhibitors Grate - Injection-Molded Polyethylene Foam

PAK987 Metric Equivalent

Load Capacity UDL: 362.9 kg Sump Capacity: 230.9 L

Technical Information

Warnings & Restrictions:

Flammables Notice

If using this product with flammable liquids, please consider the regulations that apply to storage and handling of flammable liquids and the safety of this application, specifically flammable vapors, static discharge and heat sources. For further assistance, please call Technical Services.

Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps, be designed to keep spilled liquids from remaining in contact with the container, prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers, or the volume of the largest container, whichever is greater."

40 CFR 122.26 - When applying for a National Pollutant Discharge Elimination System (NPDES) permit, facilities must have a plan in place that describes actions, procedures, control techniques, management practices and equipment available to prevent illegal discharge of pollutants into waterways.

40 CFR 112.7 - SPCC planning requirements state that facilities subject to these regulations must have written plans in place discussing the products, countermeasures and procedures that are in place, or will be taken by the facility to prevent discharge of oil into waters of the United States.

Technical Documents:

(Available at newpig.com/International)

Product Data Sheet (PDS)
Chemical Compatibility (CCG)





PAK987 Accessories

You might like		Item Number
	PIG® Poly Loading Ramp	PAK989
40	Ball Valve	DRM984



By Phone: +1-814-684-0133 Online: newpig.com/International

Email: hothogs@newpig.com