PIG® Heavy-Duty Poly Spill Containment Pallet

#PAK604 - Holds 2 Drums • Use With Plastic & Steel Drums • 66 gal. Sump Capacity







The strongest pallets you can buy won't buckle or bow, even under the heaviest loads! Guaranteed for life.

- •
- The strongest, most durable containment pallets you can buy won't buckle or bow. We guarantee it.
- Strong enough for long-term storage of liquids with high specific gravities
- Innovative design transfers weight to load-bearing channels to maximize capacity
- Molded-in sump catches leaks, drips and spills to help you comply with regulations and keep your storage areas clean and safe
- Low height means loading and unloading require less effort and drum tops are within easier reach
- Low-density polyethylene (LDPE) construction resists UV rays, rust, corrosion and most chemicals
- Textured grating adds traction and lifts out for easy sump access
- Optional drain plug lets you empty sump without removing drums or grating
- 2-way forklift entry allows easy movement from either direction (loaded or unloaded)
- We test all of our PIG Containment Pallet designs at max load for months to ensure they can handle full capacity at your facility

PAK604 Product Option Information

Item #	Description	Dimensions	Weight
PAK604-BK-WD	Black, With Drain	40" W x 66" L x 8.75" H	80 lbs.
PAK604-BK-WOD	Black, Without Drain	40" W x 66" L x 8.75" H	80 lbs.

Metric Equival	ent Description	Dimensions	Weight
PAK604-BK-WD	Black, With Drain	101.6cm W x 167.6cm L x 22.2cm H	36.3 kg
PAK604-BK-WOD	Black, Without Drain	101.6cm W x 167.6cm L x 22.2cm H	36.3 kg

PAK604 Specifications

Recycled Content: 38.3% Post-Industrial Recycled Polyethylene

Load Capacity UDL: 4500 lbs. Sump Capacity: 66 gal.

Containment Type: Containment Pallet

Double-Stackable Unit: No

Drain: Optional Drain

Fork Truck Access: Two-Way Fork Access, Can Move Loaded

Grates: (1) 52" L x 26" W Grate

Groundable for Flammables: No **Number of Containers:** 2 Drums

Type of Container: Plastic & Steel Drums

Sold as: 1 each # per Pallet: 10

Composition: Sump - LDPE w/ UV Inhibitor

Grate - Polyethylene

UNSPSC: 24101905

PAK604 Metric Equivalent

Load Capacity UDL: 2041.2 kg Sump Capacity: 249.8 L

Technical Information

Warnings & Restrictions:

Flammables Notice

If using this product with flammable liquids, please consider the regulations that apply to storage and handling of flammable liquids and the safety of this application, specifically flammable vapors, static discharge and heat sources. For further assistance, please call Technical Services.

Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps, be designed to keep spilled liquids from remaining in contact with the container, prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers, or the volume of the largest container, whichever is greater."

40 CFR 122.26 - When applying for a National Pollutant Discharge Elimination System (NPDES) permit, facilities must have a plan in place that describes actions, procedures, control techniques, management practices and equipment available to prevent illegal discharge of pollutants into waterways.

40 CFR 112.7 - SPCC planning requirements state that facilities subject to these regulations must have written plans in place discussing the products, countermeasures and procedures that are in place, or will be taken by the facility to prevent discharge of oil into waters of the United States.

Technical Documents:

(Available at newpig.com/International)

Product Data Sheet (PDS)
Chemical Compatibility (CCG)





PAK604 Accessories

You might like... Item Number



PIG® Steel Loading Ramp With Non-Slip Poly Grate

PAK603



PIG® Poly Loading Ramp

PAK734



By Phone: +1-814-684-0101

Online: newpig.com/International

Email: hothogs@newpig.com



