


PIG® Grippy® Absorbent Mat

MAT3250 Mediumweight, 32" x 50', (1) 32" x 50' mat per roll



Make the switch to the mat that sticks! Absorbent runner helps prevent slips, trips and falls around workstations and walkways near machinery in industrial facilities.

- Adhesive-backed absorbent mat stays exactly where you put it with no shifting, bunching up or flipping over to prevent slips, trips and falls in workstations and around machinery
- Proprietary adhesive sticks to the floor with a super-tight grip, but peels up easily for quick changeouts; reduces cleanup time to make your facility more productive
- Sticks to most commercial floor surfaces including concrete, VCT, linoleum, ceramic tile, quarry tile and laminate flooring
- Tough, spunbond top layer with heavy-duty zigzag stitching stands up to foot and light-wheeled traffic as well as heavy equipment driveovers; keep mat in service until it's saturated or shows signs of wear
- Eight layers of fine-fiber polypropylene safely absorb leaks, drips and overspray of oils, coolants, solvents and water
- Traps oil, grease and grime to keep them from being tracked around
- 32" x 50' roll provides enough length to create continuous coverage and absorbency in oily areas near machines and equipment
- Leakproof backing prevents absorbed liquid from soaking through to the floor
- Dark color hides grime so the mat looks cleaner longer
- Easy to cut and install: just roll it out, stick it down and smooth it out
- Tested and Certified by the National Floor Safety Institute (NFSI): when used as part of your floor safety program, high-traction surfaces such as PIG Grippy Absorbent Mat have been proven to reduce slip-and-fall claims by as much as 90%



Backing Material	Adhesive-Backed
Fluid Absorbed	Oils, Coolants, Solvents, Water – Universal
Color	Blue
Dimensions	32" W x 50' L
Recycled Content	25% or more Recycled Content
Absorbency	Up to 5.25 gal. per roll
Durability Level	Heavy Foot Traffic; Drive-Over
Industry	Industrial Facilities; Shops & Garages
Mat Quantity/Length	(1) 32" x 50' mat per roll
Mat Weight/Absorbency Level	Mediumweight
Storage Temp Range	Store between 32°F and 120°F
Temperature Limit	Surface temps from 55°F to 120°F
Walking Surface	Absorbent Top
Sold as	1 roll
Weight	12 lbs.
New Pig Patent	Patent Pending
# per Pallet	28

Composition	Absorbent - Polypropylene Stitching - Polyester Adhesive Backing - Proprietary Adhesive Material
--------------------	--

UNSPSC	47131901
---------------	----------

Pigalog® Page Number	<u>Page 23</u>
-----------------------------	--------------------------------

Metric Equivalent

Absorbency	Up to 19.9 L per roll
Dimensions	81.3cm W x 15m L
Weight	5.4 kg

Technical Information

Certifications, Approvals and Ratings	NFSI Certified,ANSI B101.1- 2009,Meets NFPA 99 Static Decay and Resistivity Requirements
--	--

Technical Documents

[PIG Grippy Mat](#)

[PIG® GRIPPY® ABSORBENT MAT PRODUCT DISCLAIMER & WARRANTY INFORMATION](#)

[Static Coefficient Of Friction \(SCOF\) Testing](#)

[How to use PIG Grippy Absorbent Mat](#)

[Case Study - General Cable](#)

[White paper – Slip & Fall Prevention Secrets](#)

PIG® Grippy® Absorbents

29 CFR 1910.22(a)(2)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com